

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (withdrawn) A control system for a hydrostatic unit having a swashplate comprising:  
an electronic means for producing a dithered output signal;  
a pressure control adapted to receive the dithered output signal  
and position the swashplate.
2. (withdrawn) The control system for a hydrostatic unit of claim 1 wherein the electronic means is a microprocessor.
3. (withdrawn) The control system of claim 2 wherein the microprocessor receives information from a set point command signal.
4. (withdrawn) The control system of claim 2 wherein the microprocessor receives information from a feedback sensor.
5. (withdrawn) The control system of claim 1 wherein the pressure control is a flapper nozzle style pilot valve with two boost spools.
6. (withdrawn) The control system of claim 1 further comprising:  
a servo system operably connected to the pressure control and swashplate.

7. (currently amended) A method of controlling the angle of a swashplate of a hydrostatic unit having a swashplate comprising steps of:

generating an electric signal based on a set point signal;  
receiving the electric signal in a microprocessor;  
interpolating the information from the electric signal using an algorithm contained in the microprocessor;

sending an output signal that is superimposed with a dither signal from the microprocessor to a pressure control;

~~dithering the output signal; and~~

generating a ~~dithered~~ pressure signal in ~~from~~ the pressure control that displaces the swashplate.

8. (original) The method of claim 7 wherein the set point signal is generated by measuring an operational parameter.

9. (original) The method of claim 8 wherein the operational parameter is the angle of the swashplate.

10. (withdrawn) The method of claim 7 wherein the algorithm is a PID type algorithm.

11. (withdrawn) The method of claim 7 wherein the algorithm is a PID + feed forward algorithm.

12. (withdrawn) The method of claim 7 wherein the algorithm is a KIDT1 algorithm.

13. (withdrawn) The method of claim 7 wherein the pressure control is a flapper nozzle style pilot valve with two boost spools.

14. (original) The method of claim 7 wherein the pressure control is a flapper nozzle style pilot valve with one boost spool.

15. (withdrawn) The method of claim 7 wherein the pressure control is a flow control.

16. (withdrawn) The method of claim 7 wherein the pressure control is comprised of two pressure controls.

17.-18. (cancelled)

19. (withdrawn) A control system for a hydrostatic pump having a swashplate comprising:

a feedback sensor adapted to sense the angle of the swashplate;  
a microprocessor adapted to receive information from the  
feedback sensor and produce a dithered output signal;  
a pressure control adapted to receive the dithered output signal  
and position the swashplate.

20. (withdrawn) The control system of claim 19 wherein the microprocessor is also adapted to receive information from a set point command signal.

21. (new) The method of claim 7 further comprising the step of receiving a feed back signal within the microprocessor that is dependent on an angle of the swashplate.

22. (new) The method of claim 21 wherein the feedback signal and set point signal are averaged by the microprocessor.